SUNMI T2s LITE Desktop POS

Flexible forms bring abundant experience

Performance breakthroughs on your fingertips.

High performance octa-core processor, up to 2.2Ghz. Equipped with large-capacity memory of 3GB RAM + 32GB ROM, T2s LITE allows you to experience unparalleled operation smoothness.

Anti-interference touch screen.

To realize your demand on worry-free touch experience in various environments, even near high-power devices, we employ an industrial-grade touch chip which is more resistant to EMI.

Unlock more possibilities with a VESA mount.

T2s LITE can be mounted with a VESA mount, enabling more applicable scenarios. For example, it can be used as a kitchen display of a KDS, greatly improving the restaurant operational efficiency.



Optional Accessories

NFC&MSR Card Reader

For NFC card reading and magnetic stripe card reading.



VESA mount

For more space-saving installation and more flexible use.







15.6"

Main: 15.6" FHD, 1920*1080



15.6" +10.1"

Second: 10.1" HD, 1024*600



15.6" +15.6"

1920*1080 Second: 15.6" FHD, 1920*1080



T2s LITE Tech Specs

Model Approved

Config 1: L1571 (Single-Display Version) Config 2: L1572 (Dual-Display (small + big) Version) Config 3: L1573 (Dual-Display (big + big) Version)

os

Android 9.0 SUNMI OS

CPII

Kryo-260, Octa-core up to 2.2GHz

Memory

32GB ROM + 3GB RAM 64GB ROM + 4GB RAM (optional)

Camera

Face Recognition camera or normal camera (only for configuraion 2&3)

Display

Configuration 1: Main: 15.6" FHD, 1920*1080 Capacitive multitouch screen Configuration 1: Mail: 13.0 FHD, Configuration 2: Main: 15.6" FHD, Second: 10.1" HD, 1920*1080 1024*600 Configuration 3: Main: 15.6" FHD, 1920*1080 Second: 15.6" FHD, 1920*1080 Capacitive multitouch screen

Speaker

Bluetooth

Buttons

1* power button 2* volumn button

External Storage Card

Support Micro SD (TF) Up to 64GB

SIM Card Slot

1* Micro SIM (optional)

LAN

LAN 100M

Network

Wi-Fi

IEEE 802.11 a/b/g/n /ac

Interface

1* RJ11 Serial port 1* RJ12 Cash drawer port 1* RJ45 LAN port

- 1* Audio jack
- 1* Power port 1* Micro-USB (debug)

Power Adapter

Input: AC100 ~ 240V/1.5A Output: DC24V/1.5A

Dimensions

430*382*215mm

Weight

Configuration 1: 4.5 Kg Configuration 2: 5.1 Kg Configuration 3: 6.8 Kg

Environment

Storage temperature: -20°C ~ 60°C